KÖSTER Waterproofing Systems

KÖSTER Filler Fine

Technical Data Sheet CT 710 020

Issued: 2020-09-21

Special filler for floor coatings resistant to mechanical stress

Features
KÖSTER Filler Fine is a special, solvent-free, mineral filler that can be added generating little dust, to aqueous and solvent-free reaction resin systems during mixing, improving the mechanical properties while achieving economically high layer thicknesses.

Technical Data

Largest grain size	0,1 mm
Bulk density	1,31 g/cm^3
Color	ligth grey

Fields of Application
KÖSTER Filler Fine is incorporated into aqueous and solvent-free reaction resin systems to build up thick layers without negatively affecting the flow properties.

Substrate
Consult the system data sheets for the respective product systems or the technical data sheet for the associated product.

Application
Consult the system data sheets for the respective product systems or the technical data sheet for the associated product.

Consumption
Depending on application; bulk density: 1.31 g/m^3

Cleaning
Consult the system data sheets for the respective product systems or the technical data sheet for the associated product.

Packaging

CT 710 020	20 kg bucket

Storage
Shelf life is at least 2 years when stored dry and pressure-free in the original sealed container.

Related products

KÖSTER CT 215 Universal Floor	Prod. code CT 215

CT - Coatings

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.

KÖSTER BAUCHEMIE AG • Dieselstraße 1-10 • D-26607 Aurich • Tel. 04941/9709-0 • Fax -40 • info@koester.eu • www.koester.eu